



CUSHMAN[®]



HAULER[®] 800X

MAKE TOUGH JOBS A WALK IN THE PARK.

The Cushman[®] Hauler[®] 800X features a lifted suspension that can take on bumps and ruts without breaking a sweat. The Hauler 800X can be equipped with an optional limited slip differential for enhanced traction on wet or loose terrain, without damaging turf. If spot maintenance and debris management are critical to keeping your course in pristine condition, the Hauler 800X is the vehicle designed for you.

LET'S WORK.[®]

13.5HP
KAWASAKI
GAS

800LB
LOAD
CAPACITY

48V
ELECTRIC

17MPH
SPEED



CUSHMAN® HAULER® 800X



HIGHER GROUND CLEARANCE



AGGRESSIVE TIRES



CANOPY



ROTO MOLDED BED

OPTIONS & ACCESSORIES

- Limited Slip Differential
- Locking Glove Box
- Windshield
- Canopy
- Taillights
- Brakelights
- Ball Hitch
- High Altitude Jetting
- Grab Handle
- Rearview Mirror
- Body Color (Patriot Blue, Forest Green, Ivory, Bright White, Inferno Red, Steel Blue, Metallic Charcoal, Flame Red, Electric Blue, Platinum, Yellow, Orange or Custom Options)
- Turn Signal with Four-Way Flashers
- Weather Enclosure

	ELECTRIC	GAS
BODY & CHASSIS		
FRAME	Welded Steel with DuraShield™ Powder Coat	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO (front), Steel Base Coat/Clear Coat (rear)	Injection Molded TPO (front), Steel Base Coat/Clear Coat (rear)
STANDARD COLOR	Forest Green	Forest Green
DIMENSIONS		
OVERALL LENGTH	107 in (272 cm)	107 in (272 cm)
OVERALL WIDTH	48.5 in (124 cm)	48.5 in (124 cm)
OVERALL HEIGHT	71.6 in (182 cm)	71.6 in (182 cm)
WHEEL BASE	65.5 in (166 cm)	65.5 in (166 cm)
FRONT WHEEL TRACK	37.0 in (94 cm)	37.0 in (94 cm)
REAR WHEEL TRACK	38.0 in (97 cm)	38.0 in (97 cm)
GROUND CLEARANCE	5.5 in (14 cm)	5.5 in (14 cm)
CARGO BOX CAPACITY	5.9 cu ft (0.17 m ³)	5.9 cu ft (0.17 m ³)
POWER		
POWER SOURCE	48V DC	4-cycle, 24.5 ci (401cc) Cylinder
VALVE TRAIN	Shunt Wound	Single Cylinder OHV
HORSEPOWER (KW)	3.0 hp (2.2 kW) Continuous	13.5 hp (9.7 kW) Exceeds SAE J1940 Std.
ELECTRICAL SYSTEM	48V	Starter/Generator, Solid-State Regulator
BATTERY (QTY/TYPE)	Six 8V Deep Cycle	One 12V Maintenance Free
KEY OR PEDAL START	Pedal Start	Pedal Start
OIL FILTER	n/a	Spin-On
COOLING SYSTEM	n/a	Air Cooled
FUEL CAPACITY	n/a	5.6 Gallon (21.6 L) Tank
DRIVE TRAIN	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
TRANSAXLE	Differential with Helical Gears	Differential with Helical Gears
GEAR SELECTION	Dash Mount F-N-R Switch	Forward-Reverse
REAR AXLE RATIO	12.44:1	11.42:1(Forward) 15.78:1(Reverse)
PERFORMANCE		
SEATING CAPACITY	2 Person	2 Person
CURB WEIGHT	1050 lb (457 kg)	850 lb (385 kg)
BED LOAD CAPACITY	500 lb (227 kg)	400 lb (180 kg)
VEHICLE LOAD CAPACITY	800 lb (360 kg)	800 lb (360 kg)
SPEED	17 mph ± 0.5 mph (27.3 kph ± 0.8 kph)	17 mph ± 0.5 mph (27.3 kph ± 0.8 kph)
TOWING CAPACITY	475 lb (215 kg) max	720 lb (327 kg) max
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	18.9 ft (5.8 m)
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack and Pinion	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	20 x 8.00 -10	20 x 8.00 -10