

HAULER® PRO-X

GET MORE MILEAGE OUT OF EVERY WORK DAY.

Stand back and let the new Hauler® PRO-X raise your expectations on what a 72-volt AC powertrain can do. With its 50-mile range, silent operation and lifted suspension, the Hauler PROX will help you and your team work seamlessly without disrupting play. Outstanding energy efficiency, low operational costs and a dash that can accommodate everything from an iPad to a radio, the Hauler PRO-X is equipped for action. So throw a spreader in the bed, load up the crew and let's work!

72v	1200LB
Ac	Tow
Electric	Capacity
12 CU FT	900LB
CARGO	LOAD
BED	Capacity

LET'S WORK.®






HAULER® PRO-X









OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- Flexible Tool Clamps
- L-Track Aluminum Bed System
- Tie Down D-Loops
 Weather Enclosure
- USB Outlet

•	12-Volt Outlet
•	Canopy Storage Net
	Pruchquard

- BrushguardROPS-Certified Ball Cage
- Weather Enclosure
- Rearview Mirror
- Color Options
- ROPS-Certified Cab

BODY & CHASSIS		
FRAME	Welded Steel with DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO, Painted	
STANDARD COLOR	Forest Green	
DIMENSIONS		
OVERALL LENGTH	119 in (302.26 cm)	
OVERALL WIDTH	50 in (125.48 cm)	
OVERALL HEIGHT W/CANOPY	77 in (196 cm)	
WHEEL BASE	78 in (197 cm)	
FRONT WHEEL TRACK	38.0 in (96.56 cm)	
REAR WHEEL TRACK	38.0 in (96.56 cm)	
GROUND CLEARANCE	7.2 in (18.29 cm)	
CARGO BOX CAPACITY	12 cu ft (0.340 m ³)	
POWER		
POWER SOURCE	72-Volts	
MOTOR TYPE	AC Induction	
HORSEPOWER (KW)	22.4HP (16.7 kW) - Measured at Peak Torque	
ELECTRICAL SYSTEM	72 Volt	
BATTERY (QTY/TYPE)	Nine 8-Volt Deep Cycle	
BATTERY CHARGER	900 Watt 72V DC	
KEY OR PEDAL START	Pedal	
DRIVE TRAIN	Motor Shaft Direct Drive	
TRANSAXLE	Differential with Helical Gears	
SPEED CONTROLLER	350 Amp AC	
GEAR SELECTION	Forward-Neutral-Reverse	
REAR AXLE RATIO	17:1	
PERFORMANCE		
SEATING CAPACITY	2 Person	
CURB WEIGHT	1513 lb (686 kg)	
BED LOAD CAPACITY	500 lb (227 kg)	
VEHICLE LOAD CAPACITY	900 lb (408 kg)	
SPEED	16.5 mph +/- 0.5 mph (26.6 kph +/- 0.8 kph)	
TOWING CAPACITY	1200 lb (544 kg) max	
OUTSIDE CLEARANCE CIRCLE	24.0 ft (7.3 m)	
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack and Pinion	
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum	
PARKING BRAKE	Self-compensating, Single Point Engagement	
FRONT/REAR TIRES		

CUSHMAN°