

# E-Z-GO® 72-VOLT FREEDOM® TXT®

EZGO

# **ENHANCED POWER AND CONVENIENCE**

Cruise the neighborhood in style. The redesigned Freedom TXT boasts a new body, higher ground clearance, and the increased power of a 72-Volt AC drivetrain. With enhanced, sport-inspired handling, unmatched energy efficiency and convenience, you're ready for wherever the day may bring. Go further and get the most out of your day.

## **STANDARD FEATURES**

- ▶ 10-in turf tires
- ► LED headlights
- ► Taillights and brakelights
- ► Sun canopy
- ► Turn Signals
- Integrated cup, ball & tee holders
- State of charge meter
- 72-volt battery charger
- ► USB port



#### www.ezgo.com

#### ELECTRIC

DIMENSIONS Overall Length Overall Width Overall Height (w/o roof) Overall Height (w/ roof) Wheel Base Front Wheel Track Rear Wheel Track Ground Clearance @ Differential

# POWER Power Source Motor Type Horsepower (kW) Electrical System Batteries (qty/type) Key or Pedal Start Battery Charger Speed Controller Drivetrain Transaxle Direction Selector Rear Axle Ratio PERFORMANCE Seating Capacity

Dry Weight (w/o batteries) Curb Weight Vehicle Load Capacity Outside Clearance Circle Speed (level ground)

### **STEERING & SUSPENSION**

Steering Suspension (front & rear) Brakes Parking Brake

Tires

#### Tire Pressure

**BODY & CHASSIS** 

Frame

Body & Finish

Available Body Colors

Standard Seat Color

Optional Seat Colors

93.5 in (238 cm)         47.0 in (119 cm)         46.5 in (118 cm)         67.5 in (171 cm)         66.0 in (168 cm)         34 in (86 cm)         38.5 in (98 cm)         4.5 in (11 cm)         72 Volt DC         72 Volt AC         22.4 HP (16.7 kW)         72 Volt Deep Cycle         Pedal         72 V, 1200 W         350 Amp         Motor Shaft Direct Drive         Hardened Helical Gears         Body Mounted FNR         16.99:1         2-Passenger         573 lb (260 kg)         1200 lb (544 kg)         800 lb (360 kg)         19 ft (5.8 m)         Eco Mode: 14.5 mph (23.3 kph)         Freedom Mode: 19.5 mph (31.4 kph)         Self-Compensating Rack and Pinion         Leaf Springs with Hydraulic Shock Absorbers         Rear Wheel Mechanical Self-Adjusting Drum
46.5 in (118 cm)         66.5 in (171 cm)         66.0 in (168 cm)         33 in (86 cm)         33.5 in (98 cm)         4.5 in (11 cm)         72 Volt DC         72 Volt AC         22.4 HP (16.7 kW)         72 Volt         Six, 12 Volt Deep Cycle         Pedal         72 V, 1200 W         350 Amp         Motor Shaft Direct Drive         Hardened Helical Gears         Body Mounted FNR         16.99:1         2-Passenger         573 lb (260 kg)         1200 lb (544 kg)         800 lb (360 kg)         19 ft (5.8 m)         Eco Mode: 14.5 mph (23.3 kph)         Freedom Mode: 19.5 mph (31.4 kph)         Self-Compensating Rack and Pinion         Leaf Springs with Hydraulic Shock Absorbers
67.5 in (171 cm)         66.0 in (168 cm)         334 in (86 cm)         38.5 in (98 cm)         4.5 in (11 cm)         72 Volt DC         72 Volt AC         22.4 HP (16.7 kW)         72 Volt         Six, 12 Volt Deep Cycle         Pedal         72 V, 1200 W         350 Amp         Motor Shaft Direct Drive         Hardened Helical Gears         Body Mounted FNR         16.99:1         2-Passenger         573 lb (260 kg)         1200 lb (544 kg)         800 lb (360 kg)         19 ft (5.8 m)         Eco Mode: 14.5 mph (23.3 kph)         Freedom Mode: 19.5 mph (31.4 kph)         Self-Compensating Rack and Pinion         Leaf Springs with Hydraulic Shock Absorbers
66.0 in (168 cm)         34 in (86 cm)         38.5 in (98 cm)         4.5 in (11 cm)         72 Volt DC         72 Volt AC         22.4 HP (16.7 kW)         72 Volt AC         22.4 HP (16.7 kW)         72 Volt Deep Cycle         Pedal         72 V, 1200 W         350 Amp         Motor Shaft Direct Drive         Hardened Helical Gears         Body Mounted FNR         16.99:1         2-Passenger         573 lb (260 kg)         1200 lb (544 kg)         8000 lb (360 kg)         19 ft (5.8 m)         Eco Mode: 14.5 mph (23.3 kph)         Freedom Mode: 19.5 mph (31.4 kph)         Self-Compensating Rack and Pinion         Leaf Springs with Hydraulic Shock Absorbers
34 in (86 cm)         38.5 in (98 cm)         4.5 in (11 cm)         72 Volt DC         72 Volt AC         22.4 HP (16.7 kW)         72 Volt AC         22.4 HP (16.7 kW)         72 Volt Quit         Six, 12 Volt Deep Cycle         Pedal         72 V, 1200 W         350 Amp         Motor Shaft Direct Drive         Hardened Helical Gears         Body Mounted FNR         16.99:1         2-Passenger         573 lb (260 kg)         1200 lb (544 kg)         800 lb (360 kg)         19 ft (5.8 m)         Eco Mode: 14.5 mph (23.3 kph)         Freedom Mode: 19.5 mph (31.4 kph)         Self-Compensating Rack and Pinion         Leaf Springs with Hydraulic Shock Absorbers
38.5 in (98 cm)         4.5 in (11 cm)         72 Volt DC         72 Volt AC         22.4 HP (16.7 kW)         72 Volt         Six, 12 Volt Deep Cycle         Pedal         72 V, 1200 W         350 Amp         Motor Shaft Direct Drive         Hardened Helical Gears         Body Mounted FNR         16.99:1         2-Passenger         573 lb (260 kg)         1200 lb (544 kg)         800 lb (360 kg)         19 ft (5.8 m)         Eco Mode: 14.5 mph (23.3 kph)         Freedom Mode: 19.5 mph (31.4 kph)         Self-Compensating Rack and Pinion         Leaf Springs with Hydraulic Shock Absorbers
4.5 in (11 cm)         72 Volt DC         72 Volt AC         22.4 HP (16.7 kW)         72 Volt         Six, 12 Volt Deep Cycle         Pedal         72 V, 1200 W         350 Amp         Motor Shaft Direct Drive         Hardened Helical Gears         Body Mounted FNR         16.99:1         2-Passenger         573 lb (260 kg)         1200 lb (544 kg)         800 lb (360 kg)         19 ft (5.8 m)         Eco Mode: 14.5 mph (23.3 kph)         Freedom Mode: 19.5 mph (31.4 kph)         Self-Compensating Rack and Pinion         Leaf Springs with Hydraulic Shock Absorbers
72 Volt DC 72 Volt AC 22.4 HP (16.7 kW) 72 Volt Six, 12 Volt Deep Cycle Pedal 72 V, 1200 W 350 Amp Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 22-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 13 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
72 Volt AC 22.4 HP (16.7 kW) 72 Volt Six, 12 Volt Deep Cycle Pedal 72 V, 1200 W 350 Amp Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
72 Volt AC 22.4 HP (16.7 kW) 72 Volt Six, 12 Volt Deep Cycle Pedal 72 V, 1200 W 350 Amp Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
72 Volt Six, 12 Volt Deep Cycle Pedal 72 V, 1200 W 350 Amp Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 22-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
Six, 12 Volt Deep Cycle Pedal 72 V, 1200 W 350 Amp Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 2-Passenger 573 Ib (260 kg) 1200 Ib (544 kg) 800 Ib (360 kg) 1200 Ib (544 kg) 800 Ib (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
Pedal 72 V, 1200 W 350 Amp Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
72 V, 1200 W 350 Amp Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
350 Amp Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
Motor Shaft Direct Drive Hardened Helical Gears Body Mounted FNR 16.99:1 2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
Hardened Helical Gears Body Mounted FNR 16.99:1 2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
Body Mounted FNR 16.99:1 2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
16.99:1         2-Passenger         573 lb (260 kg)         1200 lb (544 kg)         800 lb (360 kg)         19 ft (5.8 m)         Eco Mode: 14.5 mph (23.3 kph)         Freedom Mode: 19.5 mph (31.4 kph)         Self-Compensating Rack and Pinion         Leaf Springs with Hydraulic Shock Absorbers
2-Passenger 573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
573 lb (260 kg) 1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
1200 lb (544 kg) 800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
800 lb (360 kg) 19 ft (5.8 m) Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
Eco Mode: 14.5 mph (23.3 kph) Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
Freedom Mode: 19.5 mph (31.4 kph) Self-Compensating Rack and Pinion Leaf Springs with Hydraulic Shock Absorbers
Leaf Springs with Hydraulic Shock Absorbers
Leaf Springs with Hydraulic Shock Absorbers
Rear Wheel Mechanical Self-Adjusting Drum
Self-Compensating, Single Point Engagement
205/65 10 LOADSTAR
35 psi (241 kPa) Max.
Welded Steel with Powder-Coat Protection
Injection Molded TPO
Almond, Black, Burgundy, Electric Blue, Flame Red, Fores Green, Inferno Red, Ivory, Metallic Charcoal, Orange, Patri Blue, Platinum, White
Stone Beige
Black, Oyster



FRONT

**ADDITIONAL FEATURES** 

on Loadstar Tires

▶ 2-in lift

Front bumper

Oversized bag well

▶ Horn

▶ Storage compartment

► Custom 10-in Daytona wheels mounted



#### **POPULAR OPTIONS &** ACCESSORIES

- ► Fold-down windshield
- ► Weather enclosure
- ▶ Wheel covers (silver spoke & gold spoke)
- Side basket
- Permanent and temporary tow bars
- ► Rearview mirror ► LED light bar
- Bluetooth speakers

Features and specifications of vehicles subject to change without notice. Vehicles as photographed may include options not included on base model. ©2017 Textron Specialized Vehicles Inc. All rights reserved. 82546-G2 (06/2017)